

RW414364

Included accessories

1 x connection set

Optional accessories

RA498140:

Bottle support, oak wood, for RW414

RA430000:

Screw hole cover set

RA491161:

Extendable bottle tray, oak wood, RW 414

RA492160:

Tray, oak wood, for RW414

RA493060:

DECOR FRAME RA 493-060

installation accessories

RA420010:

Door lock for RW 414 and RW 464/466

RA421111:

SS doorframe 45,7cm / 18" left

RA421112:

SS doorframe 45,7cm / 18 right

RA423140:

Side trims, long

RA425110:

Vario SS handle 1131 mm

RA428111:

SS doorframe w/o handle 45,7cm / 18

RA460013:

Heating side kit 230V

RA464111:

Vent grille 45.7cm / 18 w/o filter

Vario wine climate cabinet 400 series 212.5 x 45.1 cm

RW414364

2 independently controllable climate zones. Consistent temperatures with exact control from +5 $^{\circ}$ C to +20 $^{\circ}$ C.

Humidity control.

Stainless steel interior

Fully extendable bottle trays in oak wood and solid aluminium in anthracite.

Bottle trays with hidden telescopic rails Warm white and glare-free LED light spots 5 preset lighting scenarios, selectable via TFT display

Opening assist for door with two options:

- 1. Push-to-open function for integration into handleless furniture front
- 2. Pull-to-open function to facilitate opening the door using a handle

Low-vibration operation

TFT touch display

Number of standard wine bottles: 70

Handling

TFT touch display operation.

Clear text display.

Lockable door (with door lock RA 420 010).

Technical features

Dynamic cold air distribution.

Automatic defrosting with defrost water evaporation.

Cushioned door closing system.

Activated charcoal air filter.

UV-protection.

Rest mode certified by Star-K.

When rest mode is active, the appliance can only be opened using a handle.

Open-door and malfunction alarm.

Selected digital services (Gaggenau Home Connect)

Remote control and monitoring.

Remote diagnostics.

Light scenarios.

Home network integration for digital services (Home Connect) wireless via WiFi.

The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Features

Capacity 70 bottles (based on 0.75 I standard bottles).

12 bottle trays,

- 10 fully extendable trays
- 3 suitable for storage of Magnum bottles.
 Flexible interior configuration possible by adding or removing fully extendable bottle trays.
 Storage of up to 6 Magnum bottles with standard tray configuration (12 bottle trays).
 Space for max. 13 bottle trays.

2 brilliant LED light spots with warm white, glare-free light (3500 K) in each climate zone. 5 different lighting scenarios can be selected for individual wine presentation.

Net volume 263 litres.

Consumption data

Energy efficiency class A at a range of energy efficiency classes from A+++ to G.
Energy consumption 167 kWh/year.
Noise level 42 dB (re 1 pW).

Planning notes

Flat hinge.

Door hinge right, reversible.

Door opening angle of 115° , fixable at 90° .

Max. door panel weight 76 kg.


The mains socket needs to be planned outside the built-in niche.

No transport/operation above 2000 m sea level.

Connection

Total connected load: 0.300 KW. Connecting cable 3.0 m, pluggable.







A: Suitable area for storage of magnum bottles in standard tray configuration


B: 0.75 litres

Measurements in mr




The hinge travel and resulting clearances from adjacent furniture units and handles can be found from the drawing while allowing for the thickness of the front panel. In the drawing, a furniture unit front panel thickness of 19 mm was assumed.





The maximum door panel dimensions are based on a clearance of 3 mm.

In the drawing, a unit front thickness of 19 mm and a Gaggenau unit handle of 49 mm were taken as a basis.



Based on the standard appliance height, the height of the plinth is 102 mm. Maximum plinth thickness 19 mm.

